

GAT

GAT-N SERIES ANALYTICAL "TOP-LOADING" SCALE WITH HIGH WINDSCREEN



Multipurpose high-precision scale, suitable for laboratory and industrial use.

RESOLUTION (g): 0.0001. CAPACITIES (g): 220.

The best solution
for advanced industrial
applications

TECHNICAL FEATURES

- Backlit LCD display with 8 16.5mm digits.
- Waterproof membrane keypad, with 9 keys.
- Construction: main structure in die-cast aluminium, ABS housing.
- Weight sensor with tuning fork system.
- STAINLESS steel plate, size Ø 80mm.
- Windscreen, level bubble and adjustable feet.
- Power supply: fitted with 230 Vac power supply unit as standard.
- RS232 and DIN8P port for connection to a PC, 3590 series touchscreen indicator or printer.
- USB port for connection to a PC that can be used as a virtual serial port RS232.
- Automatic calibration with built-in weights at power-up or by pressing the keys.
- Upon request:
 - calibration service and certificate;
 - CE-M approval;
 - weighing underhook to calculate the density.

FUNCTIONS

- Zeroing;
- Zero tracking;
- 6 selectable weighing filters;
- Semi-automatic tare;
- Conversion of approved units of measure: g (grams), ct (carats);
For internal use: oz (ounces), lb (pounds), ozt (troy ounces), gn (grains), dwt (pennyweight), mom (momme), msg (mesghal), tlh (Hong Kong Tael), tls (Singapore and Malay tael), tlt (Taiwan tael), tola (tola), bat (bath), mg (milligrams);
- Tolerance control with screen message concerning weight, pieces or customised units of measure and relative (LOW-OK-HIGH) or absolute (MIN-MAX) thresholds;
- Totalisation in loading and in unloading, on the net or total weight;
- Up to five recordable tares;
- 3 customisable virtual keys to choose the operating mode;
- 6 customisable virtual keys for the possible functions;
- Automatic update of the reference for the counting;
- Scale Identification number with a 10 digits ID;
- Operational messages for zero and tare execution;
- Bar graph displaying depending on the capacity;
- Energy saving rules on the screen backlight;
- Automatically bootable once the power supply unit is connected;
- 6 configurable communication serial protocols, with string sending either when the weight is stable, on demand, by pressing a key or continuously;
- Multi-user management with password protection and programmable settings, different for each user:
(1 Admin - 2 User - 1 Guest);
- Date and time can only be changed by authorized personnel.

VERSIONS

Available versions

Codice	Classe	Piatto Max (mm)	Max (g)	d (g)	M (g)*	Linearità (g) +/-	Ripetibilità (g)
GAT220N	I	Ø 80 mm	220	0,1 mg	1 mg	0,1 mg	0,1 mg

(*) CE-M divisions are obtainable only with the relative options.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784



SALES AND TECHNICAL ASSISTANCE SERVICE